

TECHNICAL DATA SHEET

General Description

FibaFuse® is the original paperless drywall tape that is easy to install and creates stronger joints compared to paper tape. The porous design eliminates bubbles and blisters, allowing compound to flow through the tape for a stronger bond.

FibaFuse is a mold-resistant glass mat drywall tape that is ideal for high-humidity and moisture-prone applications. It is easy to cut and designed to retain its folds for use on inside corners. May be applied using automatic taping or hand tools. Works with any type of compound but we recommend using an all-purpose, ready mix type.

Technical Characteristics

PROPERTY	IMPERIAL	METRIC	TESTING
Construction	Non-woven		D-3775
Fiber Type	Fiberglass (E-glass)		-
Filament Designation	M-type per ASTM D578	16 µm per ISO 2078	D-578
Widths	2-1/16 inch	5.24 cm	-
Weight	1.10 lb./100-ft ²	53.4 g/m ²	D-3776
Thickness	0.017 inch	0.432 mm	D-1777 & C-475
Warp Tensile	60 lbs./3-inch	3.50 (kN/m)	C-474
Weft Tensile	30 lbs./3-inch	1.75 (kN/m)	C-474

Properties

- Mold resistant - Testing concludes that FibaFuse scores a perfect "10" rating on ASTM D3273 mold test
- Lighter than paper tape - A 500' roll of FibaFuse is 62% lighter than an equivalent roll of paper tape
- Stronger than paper tape - 24 hours after applying a second coat of compound, FibaFuse's crack strength is 76% stronger than paper tape



Edited by:
SAINT-GOBAIN ADFORS America

SAINT-GOBAIN ADFORS America
1795 Baseline Road
Grand Island, NY 14072 USA
Tel: 716-775-3900
Fax: 716-775-3901
www.adfors.com

SAINT-GOBAIN ADFORS America reserves the right to change the information given herein without prior notice

Technical Data Sheet
Last update: 03/26/19